



14	brass nut	S205103-01	Hpb59-1	18.6g	1	M30X1.25	03 0301
13	gasket	S205101-06	POM	1.11g	1		
12	flow restrictor	P100042-00-12	POM+NBR		1		BFL-D15-1.75
11	ball joint	S247101-04	CW617N		1	NPT1/2	
10	O-ring	S201101-09	EP7118F	0.2g	1	Ø18X3	
9	connection seat	S244101-05	CW617N	60.1g	1	out thread M30X1.25 inner thread M18X1.25	03 1084
8	O-ring	S244101-06	EP7118F	0.2g	1	Ø21X2	02 0007
7	cover	S248101-02	SUS304	248g	1		03 1097
6	nut	S253101-07	SUS304	0.5g	1	M3	
5	connect part	S244101-09	CW617N	21g	1		03 1524
4	faceplate	S248101-01	SUS304	241.7g	1		03 1096
3	spray nozzle	S248102-01	SIL50H32	0.16g	54		
2	gasket	S253101-08	SILICONE (SS008F)	0.1g	1	Ø6*Ø3.1*0.5	
1	screw	S253101-09	SUS304	2g	1	M3X15	
No	name of parts	drawing No	material	weight	qty	Standard	Italy Drawing No

Note: Please apply thread seal tape (also known as plumber's tape) to all threads

in2aqua

Max-Eyth-Str. 38
71088, Holzgerlingen
Germany

Toll Free 1 800-257-6051